

Dekra
VT36 PT
Inspection Camera



One of the smallest watertight visual inspection cameras with pan-tilt function and built-in lighting in the world. With a diameter of only 36mm it is perfectly suited for all visual inspections in confined spaces.

Spectis
Robotics

Pipe inspections

Deep well inspections

Extremely compact – only 36mm diameter

Integrated LED lighting

Depth rating: 50bar/500m

Sewer inspections

Borehole inspections

Pan and tilt function

Specification

- > Image sensor: 1/3" CMOS
- > Video out: Composite Video (CVBS)
- > Resolution/lines: 600 TVL
- > Sensitivity: > 0.3 Lux
- > Lens: f=5.0 mm
- > Focus: 5 mm, infinite, motorised
- > Tilt range: 210°
- > Rotation: infinite
- > Lighting: High-power LED
- > Cover dome: Acrylic glass
- > Housing: Stainless steel
- > Dimensions: 36 mm x 90 mm (DxL)
- > Weight: 180 grams
- > Operating temperature: -15° Celsius – +50° Celsius
- > Depth rating: 50bar/500m



Images shown may not be an exact representation of the features listed.

Spectis Robotics Ltd
Unit 3, Crombie House, Grandholm Village
Bridge of Don, Aberdeen, Scotland, AB22 8BD

+44 1224 701444
info@spectisrobotics.com
spectisrobotics.com

**World-leading
Robotic Crawlers and
Camera Systems**